

PROTEUS-X

Integrated Tank Gauging

Automated Tank Monitoring and Management



KEY FEATURES

- Accepts up to 16 magnetostrictive probes
- Accepts up to 64 Bright Eye sensors
- Three built in programmable relays
- Up to 32 additional dry contact relays
- Large user friendly icons
- Easy to read leak and level alarms
- SD memory card slot (for extended logging)
- Built in web server
- E-mail and text capability
- VLD Standard
- Flash based non-volatile memory for program storage (battery not required)
- Compatible with OMNTEC PC remote tank inventory monitoring

OPTIONS

- Modbus RTU and TCP
- CITLD upgrade

A brighter future in tank gauging and leak detection has arrived with the PROTEUS-Series. Featuring advanced technology, versatility, scalability, and enhanced features like our 7-inch color touch screen. The PROTEUS-X Series can simultaneously monitor product levels, water levels, temperature, leaks, and much more in up to 16 tanks. The flexibility of PROTEUS-makes it ideal for a variety of gauging and leak detection applications.

The OEL8000IIIX accepts up to 64 of OMNTEC's Bright Eye™ (BX Series) sensors for distinguishing product from water or for simply detecting the presence of liquid. A distinct advantage of Bright Eye sensors is they are networked and utilize 4 wire bus technology.

PROTEUS-does not require sensor or probe input modules, bringing ease to ordering and installation. A built in microprocessor gives each sensor the ability to identify itself and its location, which is displayed along with alarm conditions on the display screen.

With OMNTEC's proven reliability, the PROTEUS-offers an attractive, comprehensive, and user-friendly system that can open doors to endless possibilities.



Specifications

General Information		
Electrical	Input 100-240 VAC ± 10% 50/60 Hz 50 watts (optional 12 VDC power)	
	Sensors 12 VDC @ 125 mA max	
	Probes 28 VDC	
	Low-voltage Outputs 12 VDC @ 150 mA	
	Built In Relay Outputs 120 VAC @ 0.6 amp resistive 3 SPST Failsafe	
Audio Visual Controls	Display 7-inch color graphic display touch screen	
	Audible alarm 85 dB piezoelectric horn	
	Printer 36 character; thermal	
	System status 3 LED's (OK, warning, alarm)	
Operating Temperature	20 to 140° F (-7° to 60° C)	
Compatible Sensors	B-XSeries sensors	
B-XSeries Sensor Cable	Shielded 22 AWG with drain wire (OMNTEC EC-4) maximum length 2,000 feet (610m)	
Compatible Probes	Rigid Gauging Probe	
	MTG-4* (1219mm)	
	MTG-6* (1829mm)	
	MTG-8* (2438mm)	
	MTG-10* (3048mm)	
Flexible Fixed Top Probe TG-F-* Series		
Flexible Fixed Bottom Probe MTG-FB-* Series		
MTG Probe Cable	OMNTEC EC-2 (Shielded Belden #8761) Low Inductance Equal or less than 0.2 microhenries per ft Max length 1,000 ft (305m)**	
Accessories	RD7CTS Mini-Me remote display	XB-416 4 probe 16 leak sensor output board
	RAS Series Remote annunciators	XB-400 4 probe output board
	PS-103 Thermal printer	XB-RB8 8 relay output board rated at 5 amps 120 VAC
	DPU-C Thermal paper	
Weight	20 lb. (9kg)	
Dimensions	7 x 15 x 9 inches (H x W x D) Depth dimension includes printer and bezel	
Approvals	UL; CUL	

* Number signifies shaft length and corresponds to tank diameter. Contact representative for additional lengths.

** Consult representative for longer wire runs.

Specifications subject to change without notice, verify with manufacturer.



Contact a Regional Sales Manager for more details.



Contact

ejward.com/contact/

SimplyFuel Solutions®